

6″ Rear Head Valve – Straight Flanged Outlet

The Betts' 6″ Rear Head Valve is a manual external stop valve designed to handle the challenges of hot product transportation. The valve body is welded directly into the bottom of the tank at the rear head which allows the seat and surrounding area to be fully heated by the elevated temperature of the product.

Valve MAWP: 10 psig [.69 bar]
Minimum bursting pressure: 100 psig [6.9 bar]
Max. Temp. of Aluminum Valve: +400°F [204°C]
Max. Temp. of Steel Valve: +500°F [260°C]

The Rear Head Valve's outward opening disc and unobstructed flow path is ideal for heavy, viscous, temperature-sensitive commodities. The stem and stem nut utilize ACME threads and a grease fitting for exceptional service life. The external packing gland allows for easy adjustment of the packing to ensure proper sealing. A caution label explaining the packing gland adjustment is included with the valve and should be located close to the valve in a conspicuous area of the tank.

Assembly Part Number	Valve Size and Type	Outlet Configuration	Outlet Angle	Body Material	Disc Seal Material *	Weight	Shear Section
RH6XFST-ALA	6" Rear Head. No Trough	Flanged (6" TTMA) B.C.: 8.13" [206 mm] 12 Holes: .44" [11.2 mm] dia.	Straight	Aluminum	Non-Asbestos (laminated)	37 lbs. [16.8 kg]	No
RH6XFST-MSA	6" Rear Head. No Trough	Flanged (6" TTMA)	Straight	Steel	Non-Asbestos (laminated)	52 lbs. [23.6 kg]	No

Assembly Part Number	Valve Size and Type	Outlet Configuration	Outlet Angle	Body Material	Disc Seal Material *	Weight	Shear Section
		B.C.: 8.13" [206 mm] 12 Holes: .44" [11.2 mm] dia.					
RH6XFST-ALA010	6" Rear Head. No Trough. With outlet flange 7.13" from center line.	Flanged (6" TTMA) B.C.: 8.13" [206 mm] 12 Holes: .44" [11.2 mm] dia.	Straight	Aluminum	Non-Asbestos (laminated)		No

NOTE: Valves as listed above are standard with Non-Asbestos w/graphite packing and Non-Asbestos tophead gasket. * The Disc Seal material can be designated by the last letter in the part number. See the table below. Steel trim components are standard unless otherwise noted in parts list.

* Letter Code (Use as last letter of part number)	Disc Seal Material	Temperature Rating
A	Non-Asbestos (laminated)	-20°F to +500°F [-29°C to 260°C]
T	PTFE	-20°F to +500°F [-29°C to 260°C]
V	FKM (Type A)	0°F to +400°F [-18°C to 204°C]

NOTE: Valves as listed above are standard with Non-Asbestos w/graphite packing and Non-Asbestos gasket. Change last letter in part number to designate altenate Disc Seal Material. Trim is steel unless otherwise noted in parts list.



MM-RH001 Installation & Maintenance Manual 4" & 6" Rear Head and Side Discharge Valves

EB-04-00: Important Notification for Rear Head Valves and Hot Product Valves

EB-02-24: Rear Head Valve Product Improvement and New Part Numbering Code Rollout

⚠ **WARNING**: This product can expose you to chemicals including Lead which is known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to: www.P65Warnings.ca.gov. For additional information on Betts products and Proposition 65 list please see: http://www.bettsind.com/prop-65/



RH6XFST-ALA / RH6XFST-MSA