Pneumatic Operated 6" Sliding Valve (Replaceable O-ring Seat) – Sump Flange x TTMA Flange

- Air Open / Spring Close
- Teflon Encapsulated Seats
- TTMA, ANSI, or Sump Flange Drilling

The Betts Pneumatic sliding valve meets requirements for an external self-closing stop valve. Valve does not contain a shear section. The cargo tank must protect the valve by providing suitable protection as specified in 49 CFR 178.345-8. The cylinder is air open with spring close and requires 90 psi line pressure to fully open. The PTFE encapsulated o-rings provide a positive seal for pressure or vacuum service and standard 316 stainless steel discs offer premium corrosion resistance. The adjustable packing nut with woven PTFE infused packing allows for easy stem adjustments. The air cylinder max working temperature is 250° F (121° C). A fusible plug, set to melt above 212° F (100° C), is installed in air cylinder to dump air pressure in case of fire.

Assembly No.	Description	A	B	C	D	E	Wt.
SV736****	Sump Flange x TTMA Flange	30.34" [771 mm]	37.75" [959 mm]	N/A	4.00" [102 mm]	4.00" [102 mm]	42.0 lb. [19.1 kg]

**** Last four letters of part number designates material of construction as shown below:

Example Assembly

SV736SSTS

(Pneumatic Operated 6" Sliding Valve (Replaceable O-ring Seat) - Sump Flange x TTMA Flange)

Disc Materials
MSTS = Steel Body with 316 Stainless Stem & Gates
SSTS = 316 Stainless Body, Stem & Gates

Disc Materials	Flange Adaptations per TTMA recommendations and grooved outlets per MIL-C-10387B.

** MAWP certified for new valves only. Seat/disc damage or wear may reduce sealable MAWP.





Flange x Flange Thread x Flange



Flange x Sump

Teflon Accordion Packing

Use suffix "008" for valve less actuator. A heat tube option is available for 4″ and 6″ sizes by adding suffix "J" to end of part number. (Heat tube MAWP = 150 psi)

Body Material	Valve MAWP**	Min. Burst Pressure	Temp. Range
Steel or Stainless	50 psi [3.4 bar]	200 psi [13.8 bar]	-40°F to 400°F [-40°C to 204°C]

NOTE: Valve should NEVER be heated with flame

EB-1-15: Important Notification for Gate/Sliding Valves Used in Hot Service Application

⚠ **WARNING**: This product can expose you to chemicals including Chromium (hexavalent compounds) which is known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to: www.P65Warnings.ca.gov. For additional information on Betts products and Proposition 65 list please see: http://www.bettsind.com/prop-65/